

1. SPECIFICATIONS

(EW201S15. EW201S20. EW201S25/ EW203S15. EW203S20.EW203S25)

1-1. CONTROL PANEL

Model / Diameter of gas pipe	1 Alarm signal input			3 Alarm signal input		
	EW201S15	EW201S20	EW201S25	EW203S15	EW203S20	EW203S25
	15A	20A	25A	15A	20A	25A
Power supply	AC 220V .230V. 50Hz. 60Hz					
Operating temperature	0~40°C					
Operating humidity	95% Rh					
Current output (Actuating)	DC 12V					
Audible alarm	Buzzer sound (about 70dB)					
Alarm input	DC 5~18V					
Dimensions	140x148x54mm					
Weight	430			446g		

1-2. SHUTOFF DEVICE

Diameter of gas pipe	15A	20A	25A
Operating power	DC 12V		
Valve type	Ball valve use		
Deceleration ratio	2,330:1		
Shutoff time	10sec		
Open & Close	90°		
Gear material	Kocetal		
Housing material	Gear box: ABS / Clamp: Nylon glass		
Operating temperature / Operating humidity	-10°C~40°C / 95% Rh		
Wiring	2Wire RED (+) BLACK (-) 1channel		
Mounting	Clamping at pipe		
Dimensions & Weight	70x115x138mm 332g	70x115x140mm 326g	70x115x155mm 360g